

REGULATORS — SP4

OCEANIC
PRODUCT
DATA SHEET



PRODUCT DETAILS

ONE MOVING PART

The advanced design of the SP4 PISTON First Stage utilizes one moving part (the piston) during operation. This helps reduce internal wear, leading to more consistent performance between service intervals and lower maintenance costs.

4 LOW PRESSURE PORTS

4 Low pressure ports allow for convenient routing of all low pressure hoses.

DIN OR USA YOKE

The Unbalanced Piston First Stage is available standard with your choice of either a 330 BAR DIN or USA Yoke fitting. A convertible yoke is also available that can convert a DIN fitting to a USA Yoke without the use of tools.



NITROX COMPATIBILITY

Factory cleaned and assembled in a clean room environment with special o-rings, halo-carbon based lubricants and color-coded for easy identification, the SP4 PISTON NITROX gives you all you need in a reliable Nitrox-ready regulator

TECHNICAL SPECIFICATIONS

FACTORY SET INTERMEDIATE PRESSURE

140 psi +/- 5 psi

LUBRICANT

Christo-Lube(r) MCG#111 used exclusively for reduced friction and superior performance

WEIGHT

1 pound, 9.2 ounces

OCEANIC
PRODUCT
DATA SHEET

